Solar Sync® Delay feature allows adjustments to be postponed

· Cycle and Soak feature built in:

· One touch manual start and advance

for up to 99 days

· Added knockouts for

• Rain sensor bypass

additional flexibility

• Warranty period: 2 years

reduces runoff

PRO-C® & PCC

Number of Stations: 4 - 16, 6 & 12

Type: Modular & Fixed

FEATURES

- Number of stations:
 - Pro-C: 4 16
 - PCC: 6 & 12
- · Type:
 - Pro-C: Modular
 - PCC: Fixed
- Enclosures: Indoor or outdoor plastic Non-volatile memory
- Independent irrigation programs: 3
- Independent lighting programs: 3
- Start times per program: 4
- Max. station run time: 6 hours
- ▶ Built in Solar Sync
- ► Easy Retrieve[™] memory
- ▶ QuickCheck™
- Automatic short circuit protection
- ▶ Seasonal Adjustment: Global or automatic updates with Solar Sync
- ► Delay between stations
- ► Sensor programmability
- ► Non-Water Days

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Operating temperature: 0° F to 140° F

APPROVALS

- CE, UL, cUL, C-tick, FCC
- = Advanced Feature descriptions on pages 84



Plastic Indoor

Height: 8¼" Width: 9½" Depth: 3¾"



Plastic Outdoor

Height: 9" Width: 10" Depth: 4½"



PCM-300 and PCM-900 Expansion Modules

These modules are compatible with the new Pro-C 400 series.

PRO-C SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4				PC-SERIES STATION EXPANSION	
1 Models	2 Transformer	3 Indoor/Outdoor	4 Options	Modules	Description
PC-4 = 4-station base module controller PCC-6 = 6-Station PCC-12 = 12-Station	00 = 120 VAC 01 = 230 VAC	(blank) = Outdoor Model (internal transformer) i = Indoor Model (plug-in transformer)	(blank) = No option E = 230 VAC with European Connections A = 230 VAC with Australian Connections (outdoor models have internal transformer with cord)	PCM-900	3-Station plug-in module: Use to increase station count from 4 to 7, 7 to 10, and 10 to 13 9-Station plug-in module: Use to increase station count from 7 to 16

Examples:

PC-400 = Modular 4-Station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i - E** = Fixed 6-Station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-Station outdoor controller, Internal 120 VAC transformer, and plastic cabinet